



POS B15S- I

Luxury Touch POS System

- One screw design
- Bezel-Free True Flat PCAP touch
- MSR / I-Button / RFID / Finger printer optional
- VFD customer display / 9.7" True-Flat LED monitor optional
- Multiple choice motherboard
- Mounted / Desktop type optional
- Slim stand
- Multiple interfaces
- Easy disassemble



Specification

CPU	Intel®Celeron® Bay Trail D J1900 Quad Core 2.0G up to 2.42G, 2M Cache 10W(Fanless)	Intel®Celeron™ 3855U, Dual Core 1.60G, 2M Cache 15W(Fanless)	Intel®Core™ i3-6100U, Dual Core 2.30G, 3M Cache 15W(Fanless)	Intel®Core™ i5-6200U, Dual Core 2.80G, 3M Cache 15W
Memory	2GB DDR3 1333MHz1* SO-DIMM slot up to 4GB			
HDD	MSATA32/64/128GB SSD or 2.5" 500GB HDD			
Size / Resolution	15" TFT-LED/ 1024×768			
Touch Screen	True flat PCAP touch screen			
Windows / Linux	Windows 7 / 8 / 10, POSReady 7, Ubuntu 13.04 LTS			
Card Reader	MSR / I-Button / RFID / Finger print			
Customer Display	VFD (2*20 lines)			
2nd Display	9.7" true-flat LED monitor			
Wireless Module	802.11a/b/g/n			
I/O Interface	Rj45x1, USB2.0x6, USB3.0x1, Rs232x3, Rj11x1			
Certificates	CE, FCC Class A, RoHS, CB			
Working Temperature	0°C~40°C(32°F~104°F)			
Carton Size(mm)	425*185*420 (L*W*H)			
G.W	6.5KGS			