





POS Terminal Machine

Enhanced POS Solutions

Cost Effective designed for Hospitality Service

#Key Features

#Flat Touch Screen #Water Splash Resistant **#Easy Maintenance Tools** #Big 2nd Display Screen





Intel Celeron J1900 | Core i5



2GB | 4GB | 8GB SODIMM DDR3



M-SATA 64GB | 128GB



15" Resistive | Projective Capacitive Touch

Designed for Hospitality Service



























Product Specifications

Model	PM-K5000-D1	PM-K5500-D1
CPU	Intel Celeron Bay Trail D J1900 Quad Core up to 2.4G (2M Cache Fanless)	Intel Core i5,-3317U ,3MB Cache, up to2.60 Ghz
Chipset	Bay Trail DJ1900	I5-3317U+HM76
Memory	4GB DDR3 (up to 8GB)	4GB DDR3 (up to 8GB)
HDD	64GB/128GB MSATA SSD	64GB/128GB MSATA SSD
Interface/ Port	6xUSB / 2xCOM/ 1xPS2/ 2xAudio / 2x10/100/1000 Base-T	
Touch Monitor	15" Resistive Touch (1024x786) FLAT SCREEN Brightness 300 cd/m2 Contrast 600:1	
Dimension	Response time 8ms 300W) X 500(L) X 470 (H) mm	
Operation Condition	Temperature: up to 40 degree Humidity: 10 to 80%	
Customer Display	(VFD-K5) 20*2 lines VFD Customer Display (PM-K5100-M15) 15" LCD Flat Screen	(VFD-K5) 20*2 lines VFD Customer Display (PM-K5500-M15) 15" LCD Flat Screen
MSR	External USB MSR Track 123.	
Operating System	Window XP/7/8/10 I POS Ready 2009 / 7 / 10 IOT	





