



# POSMAC PRINT

## CP-Q3

### 80MM THERMAL PRINTER



### #Key Features

- #4MB Input Buffer Memory Avoid Order Missing
- #100K Lifespan Printhead
- #1 Million times Lifespan Cutter
- #Multi IO Port
- #Support QR & Chinese printing
- #Support Win/Linux & OPOS
- #2 Way Stand
- #Wall Mount Ready

### Designed for Hospitality Service



Food & Beverages POS



Retail & Mobile POS



Hospitality POS



<b>Model</b>	<b>CP-Q3</b>
Printing Method	Direct Thermal
Print Speed	260mm/S
Memory	Input Buffer 4MB   NV flash buffer 256k
Paper width	79.5+-0.5mm   57.5+-0.5mm
Paper Diameter	80mm
Column capacity	576dots/line or 512 dots/line
Line space	3.75mm (changeable commands)
Character size	ANK, Font A: 12x24 dots   Font B: 9x17 dots   Chinese : 24x24 dots
Barcode	UPCA/UPCE/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODEBAR/CODE 128/QR CODE/ PDF417
Code Page	PC347 (Standard Europe)   PC850 (Multilingual)   PC852 (Latin2)   PC858 (Arabic)
Print Head	Japan Brand   Lifespan 100,000 times
Auto Cutter	FULL/HALF   Lifespan 1 million times
Interface/ Port	Serial + USB +LAN
Operation Condition	Temperature: up to 60 degrees   Humidity: 10 to 80%
Drivers	Win 9X/ME/2000/XP/NT/VISTA, WIN 7/8/ 10 LINUX /OPOS
Command	Compatible with ECS/POS
Operation Condition	Temperature: up to 60 degrees   Humidity: 10 to 80%
Add On	Wall Mount   Auto Open Cover
Dimension   Weight	185(L)*140(W)*134(H) mm   1.81kg