



# POSMAC PRINT

## BP-T3B

### 80MM THERMAL PRINTER



### #Key Features

#4MB Input Buffer Memory Avoid Order Missing

#High Speed 300mm/s

#150K Lifespan Printhead

#1 Million times Lifespan Cutter

#Multi IO Port

#Support QR & Chinese printing

#Support Win/Linux & OPOS

#Wall Mount Ready

### Designed for Hospitality Service



Food & Beverages POS




Retail & Mobile POS



Hospitality POS



<b>Model</b>	<b>BP-T3B</b>	
Printing Method	Direct Thermal	
Print Speed	300mm/S	
Memory	Input Buffer 4MB   NV flash buffer 256k	
Paper width	79.5+-0.5mm   57.5+-0.5mm	
Paper Diameter	80mm	
Column capacity	576dots/line or 512 dots/line	
Line space	3.75mm (changeable commands)	
Character size	ANK, Font A: 12x24 dots   Font B: 9x17 dots   Chinese : 24x24 dots	
Barcode	UPCA/UPCE/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODEBAR/COD E93/CODE128/ QR CODE/ PDF417	
Code Page	PC347 (Standard Europe)   PC850 (Multilingual)   PC852 (Latin2)   PC858 (Arabic)	
Print Head	Japan Brand   Lifespan 150,000 times	
Auto Cutter	FULL/HALF   Lifespan 1 million times	
Interface/ Port	Serial + USB +LAN	
Operation Condition	Temperature: up to 60 degrees   Humidity: 10 to 80%	
Drivers	Win 9X/ME/2000/XP/NT/VISTA, WIN 7/8/ 10 LINUX /OPOS	
Command	Compatible with ECS/POS	
Operation Condition	Temperature: up to 60 degrees   Humidity: 10 to 80%	
Add On	Wall Mount   Auto Open Cover	
Dimension   Weight	185(L)*140(W)*134(H) mm   1.81kg	